

water pump **YP20GX**

Featuring a self-priming centrifugal pump powered by Yamaha's tough, 4-stroke, 123cc overhead valve engine, this bad boy can move up to 600 litres/minute through a hefty two-inch port. With a cast-iron volute and impeller for long life, plus heavy-duty carbon-ceramic seals for greater durability and reduced abrasion, you'll be using it for years. Other features include a Low Oil Warning System with automatic engine shut-off; Standard N.P.T. fittings, ensuring easy hose connections; a sturdy, wrap-around steel-tube frame for added protection; and electronic ignition for effortless starting.

Specifications

Engine	Self-priming, centrifugal, 4-stroke, OHV, air-cooled
Displacement	123cc
Rated/Max. Horsepower	4.0 hp @ 4000 rpm
Engine Starting	Recoil
Ignition	TCI
Oil Capacity	0.61 Litres (0.53 Imp qt)
Fuel Capacity	4.5 litres (1.0 imp. gal)
Size	50 mm (2")
Maximum Capacity	600 litres/min. (132 gal/min)
Total Head	30m (98.5 ft)
Suction Head	7m (23.0 ft)
Priming Time	120 sec @ 5 m (16.4 ft)
Dry Weight	27 kg (59.4 lbs)
Dimensions (LxWxH)	502 x 393 x 454 mm (20.8 x 15.7 x 18.2")

Hose, couplers & strainers not included with pump.

YP20GX

\$ 549.00

water pump **YP30GX**

The beast! The 171cc 4-stroke engine of the YP30GX pumps up to 980 litres/minute through its thirsty three-inch port. Do the math: that's an insane 58,800 litres per hour! Yet it's quieter and more fuel-efficient than comparable engines in its category. Die-cast aluminum pump housings mean a manageable carrying weight, but the cast-iron volute and impeller make it super-durable. The YP30GX also features electronic ignition for easy starting, an automatic Oil Warning System to protect the engine from low-oil damage, and a large muffler for quiet all-day operation.

Specifications

Engine	Self-priming, centrifugal, 4-stroke, OHV, air-cooled
Displacement	171 cc
Rated/Max. Horsepower	5.5 hp @ 4000 rpm
Engine Starting	Recoil
Ignition	TCI
Oil Capacity	0.61 Litres (0.53 Imp qt)
Fuel Capacity	4.5 litres (1.0 imp.gal)
Size	80 mm (3")
Maximum Capacity	980 litres/min (216 gal/min)
Total Head	31 m (102 ft)
Suction Head	7 m (23 ft)
Priming Time	120 sec. @ 5 m (16.4 ft)
Dry Weight	30 kg (66 lbs)
Dimensions (LxWxH)	518 x 397 x 466 mm (20.7 x 15.88 x 18.6")

Hose, couplers & strainers not included with pump.

YP30GX

\$ 649.00

